

[home](#) | [news](#) | [features](#) | [opinion](#) | [nano & society](#) | [journal highlights](#) | [directory](#) | [links](#) | [events](#) | [your news](#) | [jobs](#) | [contact us](#) | [advertising](#) |

advanced site search

news

Browse the archive

quick search

Search news archive

news

[<< previous article](#) | [more articles](#) | [next article >>](#)

Model offers route to better solar cells

21 September 2007

Scientists have used a new model to design an optical nanocomposite made of copper, silver and gold for use in solar cell applications. Such nanocomposites, which could easily be coated onto existing solar cells made from silicon, could be optimally tuned to the solar spectrum for the first time, so enhancing the light-absorbing efficiency of these devices.

"The optical response of nanocomposites made from dielectrics (like glass) containing metal nanoparticles is fascinating and important," says lead author Justin Trice of Washington University in Saint Louis. "For example, the amazing colours in ancient glass artifacts result from the strong absorption of specific wavelengths of light thanks to the metal nanoparticles inside the glass."

This so-called plasmonic absorption has been well studied and it is now known that the type of metal, particle size, shape and concentration all affect the resulting optical properties of a material. However, until now, there was no simple way to predict the optical behaviour of nanocomposites containing several different metals.

Earlier this year, Hernando Garcia at Southern Illinois University and co-workers at Washington University made an important breakthrough in this area by developing a simple and efficient model that allowed them to accurately predict the optical response of ternary nanocomposites (that is, two metals in glass). This model, published in *Phys. Rev. B*, allowed them to mix a number of different components and predict the composite's effective dielectric function. Now, the researchers have taken this work a step further and used their mixing rules to design an optimized plasmonic solar absorbing glass containing three metals.

"One of the key steps in efficient solar energy harvesting is to absorb as much of the incident solar energy as possible," explained Ramki Kalyanaraman of Washington University. "Since the Sun's emission is over a large, broadband, spectrum (see red curve in figure 1), our primary objective was to design a glass that absorbs over the entire visible range (from about 350 to 800 nm)," he told *nanotechweb.org*.




Figure 1

The researchers achieved this by identifying metals that allow plasmonic absorption at various wavelengths

NewsAlert

[Subscribe](#) to our free news alerts service, or [alter your alert settings](#)

links

Related Links

[Department of Physics at Washington University](#)

[Center for Materials Innovation at Washington University](#)

[Department of Physics, Southern Illinois University](#)

[Energy, Environmental and Chemical Engineering at Washington University](#)

[arXiv paper: In silico design of metal-dielectric nanocomposites for solar energy applications](#)

Restricted Links

[Phys. Rev. B 75 045439](#)

Related Stories

[New look for solar cells \(March 2007\)](#)

[Nanotubes light up solar cells \(January 2007\)](#)

[Titania nanotubes could boost solar cell efficiency \(January 2006\)](#)

[Nanoparticles boost solar cells \(October 2005\)](#)

within the visible range. They found that gold (which absorbs at around 400 nm), silver (500 nm) and copper (which has a broad absorption peak around 645 nm) fitted the bill. The team therefore decided to mix the three metals into silica glass using their computer model and optimized the concentration of each metal and their particle sizes using a simulated annealing global optimisation algorithm to achieve a broadband absorption that matches the shape of the Sun's emission curve (see black curve in figure 1).

[Nanoflower improves solar cell \(August 2007\)](#)

Author

[Belle Dumé](#)



[The team](#)

Although composites containing one or even two metals have already been made in experiments using techniques like ion implantation, the new model allows designs with any number of different metals, alloys and compounds. "We are currently making materials with three or more metals using a self-organization technique that will be guided by modelling and computations based on thin-film growth and laser processing," says Radhakrishna Sureshkumar of Washington University "and we hope to test the optical properties of such nanocomposites within a year."

The team now plans to assemble such nanocomposites and measure their intrinsic linear and non-linear optical properties. "We also hope to develop cost-effective and simple nanomanufacturing strategies to implement these coatings in devices such as semiconductor solar cells, optical sensors and optical modulators," state the researchers.

The work was reported in *arXiv* and was recently presented at the SPIE Optics+ Photonics conference in San Diego.

About the author

Belle Dumé is contributing editor at [nanotechweb.org](#)

E-mail to a friend

Nanotechnology Intelligence and Marketing Solutions

[home](#) | [news](#) | [features](#) | [opinion](#) | [nano & society](#) | [journal highlights](#) | [directory](#) | [links](#) | [events](#) | [your news](#) | [jobs](#) | [contact us](#) | [advertising](#) |

Tel +44 (0)117 929 7481 | Fax +44 (0)117 930 1178 | E-mail info@nanotechweb.org
[Copyright](#) © [IOP Publishing Ltd](#) 1996-2007. All rights reserved.